






# NAFS PERFORMANCE GRADE RATINGS

August 2017

All Durabuilt windows and doors have a different performance grade based on the window type, size and configuration. This guide provides base single unit window information - contact your Durabuilt sales consultant to provide a quote for your project to obtain your specific NAFS performance grade ratings.

Series	Window Type	Air	Water	Structural	PG Ratg (size)	Air leakage
 <b>Alpha Monoframe 6 1/2"</b>	Single Hung	A3/FX	470 Pa (9.75 PSF)	2160 Pa (45 PSF)	LC-PG45-H 1017x1800mm (40x71)	0.4
		A3/FX	470 Pa (9.75 PSF)	3360 Pa (70.00 PSF)	LC-PG50-H 1210x1800mm (48x71)	0.37
	Slider	A3/FX	470 Pa (9.75 PSF)	1920 Pa (40.00 PSF)	R-PG40-HS 1810x1018mm (71x40)	0.2
		A3/FX	470 Pa (9.75 PSF)	2160 Pa (45 PSF)	CW-PG45-HS 1810x1580mm (71x62)	0.29
	Picture	FX	730 Pa (15 PSF)	1920 Pa (40 PSF)	CW-PG40-FW 2130x2130mm (84x84)	0
		A3	470 Pa (9.75 PSF)	+1,920 Pa (40.0 PSF)	LC-PG40-HS-FW-HS 3175x1778mm (125x70)	0.26
 <b>Alpha Nail fin 4 1/2"</b>	Single Hung	A3/FX	360 Pa (7.50 PSF)	2160 Pa (45 PSF)	LC-PG45-H 1017x1800mm (40x71)	0.4
		A3/FX	360 Pa (7.50 PSF)	3360 Pa (70.00 PSF)	LC-PG50-H 1210x1800mm (48x71)	0.37
	Slider	A3/FX	360 Pa (7.50 PSF)	1920 Pa (40.00 PSF)	R-PG40-HS 1810x1018mm (71x40)	0.2
		A3/FX	330 Pa (6.75 PSF)	2160 Pa (45 PSF)	CW-PG45-HS 1810x1580mm (71x62)	0.29
	Picture	FX	730 Pa (15 PSF)	1920 Pa (40 PSF)	CW-PG40-FW 2130x2130mm (84x84)	0
		A3	330 Pa (6.75 PSF)	+1,920 Pa (40.0 PSF)	LC-PG40-HS-FW-HS 3175x1778mm (125x70)	0.26
 <b>Alpha 2" BM Monoframe</b>	Single Hung	A3/FX	470 Pa (9.75 PSF)	2160 Pa (45 PSF)	LC-PG45-H 1017x1800mm (40x71)	0.4
		A3/FX	470 Pa (9.75 PSF)	3360 Pa (70.00 PSF)	LC-PG50-H 1210x1800mm (48x71)	0.37
	Slider	A3/FX	470 Pa (9.75 PSF)	1920 Pa (40.00 PSF)	R-PG40-HS 1810x1018mm (71x40)	0.2
		A3/FX	470 Pa (9.75 PSF)	2160 Pa (45 PSF)	CW-PG45-HS 1810x1580mm (71x62)	0.29
	Picture	FX	730 Pa (15 PSF)	1920 Pa (40 PSF)	CW-PG40-FW 2130x2130mm (84x84)	0
		A3	470 Pa (9.75 PSF)	+1,920 Pa (40.0 PSF)	LC-PG40-HS-FW-HS 3175x1778mm (125x70)	0.26
<b>Alpha</b>	Double slider	A3/FX	220 Pa (4.50 PSF)	1680 Pa (35.00 PSF)	R-PG35-BW 1830x915mm (72x36)	0.25
		A3	730 Pa (15.00 PSF)	3360 Pa (70.00 PSF)	CW-PG70-AP 1220x820mm (48x32)	0.04
<b>Omega 750</b>	Casement	A3	730 Pa (15.00 PSF)	3360 Pa (70.00 PSF)	CW-PG70-C 815x1520mm (32x60)	0.05
		FIXED	730 Pa (15.00 PSF)	2160 Pa (45.00 PSF)	CW-PG45-FW 1830x1830mm (72x72)	0
		A3	730 Pa (15.00 PSF)	2640 Pa (55 PSF)	LC-PG55-AP 1400 mm x 1220 mm (55" x 48")	0.4
 <b>Omega 800</b>	Awning	A3	730 Pa (15.00 PSF)	2640 Pa (55 PSF)	LC-PG55-AP 1525 mm x 1015 mm (60" x 40")	0.2
		A3	730 Pa (15.00 PSF)	1920 Pa (40 PSF)	CW-PG40-C 815 mm x 2030 mm (32" x 84")	0.15
	Casement	A3	730 Pa (15.00 PSF)	1920 Pa (40 PSF)	CW-PG40-C 910 mm x 1825 mm (36" x 72")	0.1
		FIXED	730 Pa (15.00 PSF)	2150 Pa (45 PSF)	CW-PG45 FW 2135 mm x 2135 mm (84" x 84")	0.03
	Picture	FIXED	730 Pa (15.00 PSF)	2640 Pa (55 PSF)	CW-PG55 FW 1520 mm x 2740 mm (60" x 108")	0.01
		FIXED	730 Pa (15.00 PSF)	2640 Pa (55 PSF)	CW-PG55 FW 2740 mm x 1520 mm (108" x 60")	0.01
		FIXED	730 Pa (15.00 PSF)	1920 Pa (40 PSF)	CW-PG40 FW 2135 mm x 2740 mm (84" x 108")	0.01
		FIXED	730 Pa (15.00 PSF)	1920 Pa (40 PSF)	CW-PG40 FW 2740 mm x 2135 mm (108" x 84")	0.01
		FIXED	730 Pa (15.00 PSF)	1920 Pa (40 PSF)	CW-PG40 FW 2740 mm x 2135 mm (108" x 84")	0.01
 <b>Vivacé</b>	Picture	FIXED	730 Pa (15.00 PSF)	3360 Pa (70 PSF)	AW-PG70-FW 1524x2515mm (60x99)	0.11
		FIXED	730 Pa (15.00 PSF)	3360 Pa (70 PSF)	CW-PG70-FW 1524x1524mm (60x60)	0.01
	Tilt Turn	A3	730 Pa (15.00 PSF)	3360 Pa (70 PSF)	CW-PG70-DAW 1219x1803mm (48x71)	0.06
	Tilt Slide patio	A3	580 Pa (12.00 PSF)	1680 Pa (35 PSF)	CW-PG35-SD 2413x2108mm (95x83)	0.11
Swing door	A3	400 Pa (8.25 PSF)	2640 Pa (55 PSF)	CW-PG55-SHD 1016x2032mm (40x80)	0.07	

Note: Use Omega 800 information for Hybridex windows.



all about you.