

SLIDING PATIO DOORS

ENERGY PERFORMANCE & NAFS RATINGS

Durabuilt offers a selection of sliding patio doors to pair up with our Alpha, Omega and Hybridex window series. Below are the energy performance and NAFS ratings.

ECONOSTAR		
Energy Performance		
Dualpane Low E - Argon		
NBC 9.36	U-Value 1.70 Metric, SHGC .56, VT .61, ER 34, NBC2010 Zone 4, 5, 6, 7A, 7B, 8	
Energy Star Zones	1 2	
NAFS		
Size	PG Rating	Size Tested - mm (inches)
6' x 6'8"	Class R-PG40	1818 x 2020 (71 1/2" x 79 1/2") Configuration OX

THERMOGUARD		
Energy Performance		
Dualpane Low E - Argon		
NBC 9.36	U-Value 1.70 Metric, SHGC .53, VT .61, ER 33, NBC2010 Zone 4, 5, 6, 7A, 7B, 8	
Energy Star Zones	1 2	
NAFS		
Size	PG Rating	Size Tested - mm (inches)
6' x 6'8"	Class R-PG40	1819 x 2057 (72" x 81") Configuration OX
7' x 6'10"	Class LC-PG55	2205 x 2100 (86 3/4" x 82 5/8") Configuration OX
8' x 8'0"	Class LC-PG-35	2426 x 2426 (96" x 96") Configuration OX
15' x 8'0"	Class LC-PG35	4804 x 2424 (189" x 96") Configuration OXXO
Sidelite - vertical mullion	Class LC-PG30	513 x 2020 (20" x 79 1/2") Configuration O
Transom - horizontal mullion	Class LC-PG30	2830 x 920 (111" x 36") Configuration O

HYBRIDEX		
Energy Performance		
Dualpane Low E - Argon		
NBC 9.36	U-Value 1.76 Metric, SHGC .54, VT .62, ER 32, NBC2010 Zone 4, 5, 6, 7A, 7B, 8	
Energy Star Zones	1 2	
NAFS		
Size	PG Rating	Size Tested - mm (inches)
6' x 6'8"	Class R-PG50	1816 x 2064 (72" x 81") Configuration XO
8' x 8'0"	Class LC-PG30	2430 x 2430 (96" x 96") Configuration XO
9' x 6'8"	Class R-PG40	2722 x 2100 (107" x 83") Configuration OXO
9' x 8'0"	Class R-PG30	2722 x 2426 (107" x 96") Configuration OXO
9' x 8'0"	Class R-PG30	2722 x 2426 (107" x 96") Configuration XOX
11' x 6'10"	Class R-PG35	3563 x 2100 (140" x 83") Configuration OXXO
11' x 8'0"	Class R-PG25	3563 x 2426 (140" x 96") Configuration OXXO
Patio door w/ Transom	Class R-PG30	2410 x 2438 (95" x 96") Configuration O / XO